

HRX SERIES

Hydraulic Hammers



POWER. PRECISION. PERFORMANCE.

Engineered for maximum impact,
built for the toughest demolition.



MAXIMUM IMPACT

High striking energy for faster, more efficient breakdown.



BUILT TO LAST

Heavy-duty construction for extreme durability in tough conditions.



EFFICIENCY DRIVEN

Optimised performance for lower operating costs and higher productivity.



EASY SERVICE

Simple design for quick maintenance and reduced downtime.

HYDRAULIC HAMMERS

	HRX-25S	HRX-35S	HRX-55S	HRX-85S	HRX-125S	HRX-165S
Excavator class (t) ¹	1.0 - 2.5	2.0 - 4.5	4 - 7	6 - 8	7 - 14	12 - 19
Weight (kg)	130	170	360	450	640	1000
Blows (bpm)	700 - 1200	600 - 1100	500 - 900	400 - 800	400 - 800	350 - 700
Working pressure (bar)	120	120	140	150	160	170
Oil flow (l/min)	20 - 40	25 - 50	40 - 70	50 - 90	60 - 100	80 - 110
Chisel diameter (mm)	45	53	70	75	85	100

HYDRAULIC HAMMERS

	HRX-225S	HRX-265S	HRX-325S	HRX-425S	HRX-525S
Excavator class (t) ¹	19 - 24	22 - 28	27 - 38	36 - 48	42 - 56
Weight (kg)	1730	2180	2940	3600	4400
Blows (bpm)	350 - 500	350 - 500	200 - 300	150 - 300	140 - 200
Working pressure (bar)	180	180	220	230	250
Oil flow (l/min)	120 - 150	120 - 180	180 - 240	200 - 260	220 - 270
Chisel diameter (mm)	135	140	155	165	175

¹ Recommended excavator / attachment combination